

Link do produktu: <http://www.solarsystemy.pl/inwerter-sieciowy-infinisolar-48v230v-3kw-plus-1-fazowy-on-grid-off-grid-p-1137.html>



Inwerter sieciowy InfiniSolar 48V/230V 3kW Plus 1-fazowy on-grid/off-grid

Dostępność **Dostępny**

Opis produktu

Series Specifications

Model No.				
	InfiniSolar 2KW	InfiniSolar 3KW	InfiniSolar Plus 3KW	InfiniSolar 5KW
Input Data(DC)				
Max. DC Power				
	2.25 kW	3.2 kW	4.5 kW	7.5 kW
Max. DC Voltage				
	350 V	500 V	500 V	500 V
Nominal DC Voltage				
	300 V	360 V	360 V	360 V
Min. DC Voltage to Start Feed In				

120 V	150 V	150 V	150 V
-------	-------	-------	-------

Max. DC Current

15 A	13 A	18 A	15 A
------	------	------	------

MPP Voltage Range

150~320 V	250~450 V	250~450 V	250~450 V
-----------	-----------	-----------	-----------

No. of MPP Trackers

1	1	1	2
---	---	---	---

Output Data (AC)

Max. AC Power

2 kW	3 kW	3 kW	5 kW
------	------	------	------

Output AC Voltage Range

88~127 V	184~264.5 V	184~264.5 V	184~264.5 V
----------	-------------	-------------	-------------

Nominal AC Voltage

101,120,127 V	208,230,240 V	208,230,240 V	208,230,240 V
---------------	---------------	---------------	---------------

Nominal AC Current

18 A	13 A	13 A	21 A
------	------	------	------

Power Factor (cosφ)

0.99	0.99	0.99	0.99
------	------	------	------

No. of feed-in phases

1	1	1	1
---	---	---	---

Max. Efficiency

95 %	96 %	96 %	96 %
------	------	------	------

Euro Efficiency

94 %	95 %	95 %	95 %
------	------	------	------

General Data

Dimensions (h/W/D)

480x438x107 mm	480x438x104 mm	480x438x107 mm	505x440x135 mm
----------------	----------------	----------------	----------------

Weight

15.5 kg	15.5 kg	15.5 kg	18.5 kg
Operating Temperature			
-0 ~ +40 °C			
Humidity			
0-90%			
Max. Altitude			
1000 m			
Interface			
RS 232,USB			
Display			
LCD			